



HIGHLIGHTS

- More surface area than a regular air filter
- Extended surface for maximum dust holding capacity
- Low resistance
- Washable and reusable
- Rust resistant

STANDARD SIZE FILTERS

Nominal Size (Actual size 1/2" under)	Part Number	Pack Ctn/ Lbs. Ctn
16 x 20 x 1	PF16201N	12 /17 lbs.
16 x 25 x 1	PF16251N	12 /21 lbs.
20 x 20 x 1	PF20201N	12 /21 lbs.
20 x 25 x 1	PF20251N	12 /25 lbs.
24 x 24 x 1	PF24241N	12 /27 lbs.
10 x 20 x 2	PF10202N	12 /25 lbs.
12 x 24 x 2	PF12242N	12 /27 lbs.
16 x 20 x 2	PF16202N	12 /27 lbs.
16 x 25 x 2	PF16252N	12 /31 lbs.
20 x 20 x 2	PF20202N	12 /35 lbs.
20 x 25 x 2	PF20252N	12 /40 lbs.
24 x 24 x 2	PF4242N	12 /46 lbs.

CONSTRUCTION The Perm A Foam Filter consists of PPI 20 foam with aluminum expanded on both sides. The media is corrugated inbetween layers of aluminum expanded. This creates high dust holding capacity and low resistance. The media is enclosed in an aluminum frame, mitered and secured at one corner by rivets. The filter is designed for applications such as industrial, commercial, schools, office buildings, and hotels where a permanent filter is recommended. Maximum operating temperature on the Perm A Foam is 250 degrees F. Available in both standard and special sizes. Available in 3" and 4" thicknesses.

MATERIAL Frame shall be made from sheet Aluminum 3003-H14, .040 thickness.

CLEANABILITY To clean simply wash under a faucet or hose, let dry and replace.